



# AWAYWASH

## Concrete Washout System

- Concrete truck-mounted washout collection and retention system allowing to washout and transport harmful water away from construction sites.
- Capacity of 55L to top of sieve slots.
- Patented Design with EU Design registration.
- Mount with M8 Stainless Steel bolts - max screw length 15 mm + frame thickness; max frame hole  $\varnothing$  10 mm. Tighten to a max torque of 25 Nm.
- Can be retro fit.
- Do not stand on the AWAYWASH or drill into the sump.
- Empty daily at appropriate disposal/recycling sites.
- Made from 100% recyclable chemically resistant PE.
- Inspect the unit daily, repair or replace if damaged.
- Wear protective PPE especially gloves when removing the sieve and washing down.
- Designed to fit primarily on the driver side of most right hand drive vehicles.
- Before driving ensure the flexible hose is firmly fitted and locked to the spigot.
- Always empty unit & hose at temperatures  $\leq 3^{\circ}\text{C}$ .
- Watch the AWAYWASH video for typical use and advice here:  
[https://www.youtube.com/watch?v=gBjOW2z\\_eqc](https://www.youtube.com/watch?v=gBjOW2z_eqc)



CCRT-TS-YE + CCRT-K



CCRT-TS-YE + CCRT-K



CCRT-S-YE

Available from:



Toll Free: 866-837-2082  
[www.nuline.ca](http://www.nuline.ca)  
[sales@nuline.ca](mailto:sales@nuline.ca)

891 Arvin Avenue,  
 Stoney Creek, ON L8E 5N9  
 Fax: (905) 643-5380